



SUPPLYING DEMAND®

WASHER TUB TO PUMP HOSE

SD285871

IMPORTANT: Unplug your appliance and turn off power at the breaker before servicing. 

Turn off water supply. 

If you have doubts or are unfamiliar with this type of installation work, seek the services of a qualified Service Technician. Supplying Demand assumes no responsibility for the improper installation of this product.

TOOLS NEEDED:

- Pliers
- Flat head screwdriver
- Phillips head screwdriver
- Putty Knife

COMMON ISSUES:


- Leaks due to wear or damage
- Slow or no drainage due to blockage

THIS KIT INCLUDES:

- Tub To Pump Hose
- (2) Clamps



INSTALLATION INSTRUCTIONS

1. Remove the control panel
 - a. The panel is held on by screws in either the front or rear
 - i. Some models require the removal of trim covering the screws
 - ii. A putty knife may be needed to release spring clips and access the screws
 - b. After removing the screws slide the panel forward until it disengages allowing it to flip back over the machine
2. Disconnect the lid switch by depressing the clip on the wiring harness to release it
3. Remove the retaining ring clips holding the frame and body together by prying them out with the flat head screwdriver
4. Open the lid for a better hand-hold, brace the bottom of the washer with your foot, tilt the top forward roughly 45 degrees, and lift the body off of the frame
5. Using pliers unclamp the hose and disconnect it from the drain pump 
 - a. Take precaution when disconnecting the hose. Removing excess water with a wet/dry vac as well as laying down a towel is recommended.
6. Unclamp the other end of the hose and disconnect if from the tub
7. When installing the new hose one end will be stamped to signify the pump end so be sure to connect it to the pump first
 - a. Don't forget to slide the (2) clamps onto the hose before connecting it
8. After connecting the other end of the hose to the tub secure both clamps
 - a. Be careful NOT to over tighten the clamps and damage the tub or drain pump
9. Place the washer body back onto the frame
 - a. The lower lip of the body should be underneath the frame when sliding it on
 - b. Lower it down onto the (4) locking tabs once it's in position
10. Reinstall the retaining clips by pushing them into place with the flat head screwdriver
11. Reconnect the lid switch harness
12. Flip the control panel back into position and lock it into place before replacing all screws, trim, and covers