

CONDENSATE PUMP WITH AUDIBLE ALARM SDCP115

115 V, 60 HZ, 1.5A, 1 PHASE -- MAXIMUM WORK LIFT 20 GPH TO 20 FT.

SPECIFICATIONS & PERFORMANCE

| | | | |
|------------------------------|------------------------------------|------------------------------|----------|
| • HP | 1/10 HP | GPH OF WATER @ | |
| • WATTS | 80 WATTS | • 1 FT. OF HEAD | 99 |
| • VOLTAGE | 120 VAC | • 5 FT. OF HEAD | 87 |
| • AMPS | 1.5 AMP | • 10 FT. OF HEAD | 69 |
| • HERTZ | 60 Hz | • 15 FT. OF HEAD | 48 |
| • MOTOR OVERHEATER PROTECTOR | YES | • 20 FT. OF HEAD | 20 |
| • WHOLE PUMP HEIGHT (IN.) | 7 1/4" | • 22 FT. OF HEAD | 10 |
| • WHOLE PUMP LENGTH (IN.) | 11 1/4" | • 24 FT. OF HEAD | 0 |
| • WHOLE PUMP WIDTH (IN.) | 5" | • SHUT OFF (FT) | 24' |
| • TANK SIZE | 1/2 GAL. | • MAX. PRESSURE (PSI) | 10.1 PSI |
| • DISCHARGE | 3/8" BARB | • MAX. TEMP (F) | 110°F |
| • TANK MATERIAL | ABS | • ALARM | 80 dB |
| • FLOAT MATERIAL | POLYPROPYLENE | • AUTO OFF WITH DRY CONTACTS | YES |
| • SHAFT MATERIAL | S.S.304 | • FLOAT ACTIVATED | YES |
| • IMPELLER MATERIAL | GLASSFIBER FILLED POLYPROPYLENE | • CERTIFICATION AGENT | cULus |